

COMMERCIAL
INDOOR | OUTDOOR LIGHTING





JAQUAR LIGHTING

Jaquar Lighting follows in the footsteps of Jaquar Group by ensuring that every lighting product reflects Jaquar's impeccable record of superlative quality and painstaking attention to detail.

Whether it is LED Bulbs, Tubelights, Chandeliers, Landscape Lighting or Track Lights, Jaquar Lighting's LED solutions are created with a commitment to Energy Efficiency, Quality and Durability, Aesthetic Design and Customer Service.

It is a commitment powered by Jaquar Lighting's impressive list of capabilities:

- Its own NABL Accredited Laboratory for in-house testing
- All luminaires tested in accordance with latest standards for LM
- A wide range of testing equipments for thorough quality check of the products
- In-house lighting design team located at HO and at Regional Levels
- Professional lighting design software to match global standards
- Compliance with the most stringent quality standards

Jaquar Lighting's primary focus is to sustain a world class design standard, achieve the best quality in its products and offer cutting edge services apart from regular innovation and energy efficient solutions.

COMMERCIAL LIGHTING

Jaquar Lighting pushes the boundaries of commercial lighting to provide you with some of the most advanced, high performance, energy-saving LED lighting systems for the workplace. There is a wide variety of products to suit every application and light every area of any kind of commercial establishment, from workstations to conference rooms, reception areas to cabins, and small and large showrooms.

APPLICATIONS



Offices



Hotels and Restaurants



Malls



Hospitals



Residences



Banks and Institutions



Shopping Complexes

ISO Certificate



NABL Certificate



BIS Certificate



Contents

INDOOR COMMERCIAL SERIES

- DOWNLIGHTS	5
- COB-DOWNLIGHTS	15
- LED PANELS	20
- LED BATTEN-TUBES	23
- PHASED OUT ITEMS	25

DESIGNER LIGHT SERIES 28

RETAIL LIGHTING SERIES 31

INDUSTRIAL LIGHTING SERIES 37

ROADWAY LIGHTING SERIES 41

FLOODLIGHTING SERIES 44

LANDSCAPE LIGHTING SERIES 46

INDOOR COMMERCIAL SERIES



DOWNLIGHTS

Neve Plus (Round)

LED recess-mounted round panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNEP01R003XC	3	6500	20	400
LNEP01R003XN	3	4000	20	400
LNEP01R003XW	3	3000	20	400
LNEP01R006XC	6	6500	20	620
LNEP01R006XN	6	4000	20	620
LNEP01R006XW	6	3000	20	620
LNEP01R012XC	12	6500	10	880
LNEP01R012XN	12	4000	10	880
LNEP01R012XW	12	3000	10	880
LNEP01R015XC	15	6500	10	1100
LNEP01R015XN	15	4000	10	1100
LNEP01R015XW	15	3000	10	1100
LNEP01R018XC	18	6500	10	1400
LNEP01R018XN	18	4000	10	1400
LNEP01R018XW	18	3000	10	1400
LNEP01R024XC	24	6500	10	1800
LNEP01R024XN	24	4000	10	1800
LNEP01R024XW	24	3000	10	1800

3W Cutout: Ø72mm
Height: 20mm

15W Cutout: Ø180mm
Height: 20mm

6W Cutout: Ø107mm
Height: 20mm

18W Cutout: Ø206mm
Height: 20mm

12W Cutout: Ø154mm
Height: 20mm

24W Cutout: Ø275mm
Height: 20mm

DOWNLIGHTS

Neve Plus (Square)

LED recess-mounted square panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNEP01S003XC	3	6500	20	400
LNEP01S003XN	3	4000	20	400
LNEP01S003XW	3	3000	20	400
LNEP01S006XC	6	6500	20	620
LNEP01S006XN	6	4000	20	620
LNEP01S006XW	6	3000	20	620
LNEP01S012XC	12	6500	10	880
LNEP01S012XN	12	4000	10	880
LNEP01S012XW	12	3000	10	880
LNEP01S015XC	15	6500	10	1100
LNEP01S015XN	15	4000	10	1100
LNEP01S015XW	15	3000	10	1100
LNEP01S018XC	18	6500	10	1400
LNEP01S018XN	18	4000	10	1400
LNEP01S018XW	18	3000	10	1400
LNEP01S024XC	24	6500	10	1800
LNEP01S024XN	24	4000	10	1800
LNEP01S024XW	24	3000	10	1800

3W Cutout: 72 x 72mm
Height: 20mm

6W Cutout: 107 x 107mm
Height: 20mm

12W Cutout: 154 x 154mm
Height: 20mm

15W Cutout: 180 x 180mm
Height: 20mm

18W Cutout: 206 x 206mm
Height: 20mm

24W Cutout: 275 x 275mm
Height: 20mm

DOWNLIGHTS

Nero Round

LED recess-mounted designer panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNRO01R006XC	6	6500	20	700
LNRO01R006XN	6	4000	20	700
LNRO01R006XW	6	3000	20	700
LNRO01R009XC	9	6500	20	800
LNRO01R009XN	9	4000	20	800
LNRO01R009XW	9	3000	20	800
LNRO01R012XC	12	6500	10	950
LNRO01R012XN	12	4000	10	950
LNRO01R012XW	12	3000	10	950
LNRO01R015XC	15	6500	10	1100
LNRO01R015XN	15	4000	10	1100
LNRO01R015XW	15	3000	10	1100
LNRO01R018XC	18	6500	10	1400
LNRO01R018XN	18	4000	10	1400
LNRO01R018XW	18	3000	10	1400

6W Cutout: Ø74mm
Height: 13mm

15W Cutout: Ø138mm
Height: 13mm

9W Cutout: Ø74mm
Height: 13mm

18W Cutout: Ø178mm
Height: 13mm

12W Cutout: Ø138mm
Height: 13mm

Nero Square

LED recess-mounted designer panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNRO01S006XC	6	6500	20	700
LNRO01S006XN	6	4000	20	700
LNRO01S006XW	6	3000	20	700
LNRO01S009XC	9	6500	20	800
LNRO01S009XN	9	4000	20	800
LNRO01S009XW	9	3000	20	800
LNRO01S012XC	12	6500	10	950
LNRO01S012XN	12	4000	10	950
LNRO01S012XW	12	3000	10	950
LNRO01S015XC	15	6500	10	1100
LNRO01S015XN	15	4000	10	1100
LNRO01S015XW	15	3000	10	1100
LNRO01S018XC	18	6500	10	1400
LNRO01S018XN	18	4000	10	1400
LNRO01S018XW	18	3000	10	1400

6W Cutout: 80 x 80mm
Height: 13mm

15W Cutout: 115 x 115mm
Height: 13mm

9W Cutout: 80 x 80mm
Height: 13mm

18W Cutout: 154 x 154mm
Height: 13mm

12W Cutout: 115 x 115mm
Height: 13mm

DOWNLIGHTS

Areva (Round)

Low depth, recess-mounted, sleek, round downlight with aluminium die cast housing & polycarbonate diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LARV01R006XC	6	6500	10	640
LARV01R006XN	6	4000	10	640
LARV01R006XW	6	3000	10	640
LARV01R009XC	9	6500	10	830
LARV01R009XN	9	4000	10	830
LARV01R009XW	9	3000	10	830
LARV01R012XC	12	6500	10	1010
LARV01R012XN	12	4000	10	1010
LARV01R012XW	12	3000	10	1010
LARV01R015XC	15	6500	10	1200
LARV01R015XN	15	4000	10	1200
LARV01R015W	15	3000	10	1200
LARV01R018XC	18	6500	10	1380
LARV01R018XN	18	4000	10	1380
LARV01R018XW	18	3000	10	1380
LARV01R024XC	24	6500	10	1760
LARV01R024XN	24	4000	10	1760
LARV01R024XW	24	3000	10	1760

6W Cutout: Ø75mm
Height: 35mm

9W Cutout: Ø75mm
Height: 33mm

12W Cutout: Ø106mm
Height: 33mm

15W Cutout: Ø106mm
Height: 33mm

18W Cutout: Ø158mm
Height: 33mm

24W Cutout: Ø208mm
Height: 35mm

Areva (Square)

Low depth, recess-mounted, sleek, square downlight with aluminium die cast housing & polycarbonate diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LARV01S006XC	6	6500	10	640
LARV01S006XN	6	4000	10	640
LARV01S006XW	6	3000	10	640
LARV01S009XC	9	6500	10	830
LARV01S009XN	9	4000	10	830
LARV01S009XW	9	3000	10	830

DOWNLIGHTS

Areva (Square)

Low depth, recess-mounted, sleek, square downlight with aluminium die cast housing & polycarbonate diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LARV01S012XC	12	6500	10	1010
LARV01S012XN	12	4000	10	1010
LARV01S012XW	12	3000	10	1010
LARV01S015XC	15	6500	10	1200
LARV01S015XN	15	4000	10	1200
LARV01S015XW	15	3000	10	1200
LARV01S018XC	18	6500	10	1380
LARV01S018XN	18	4000	10	1380
LARV01S018XW	18	3000	10	1380
LARV01S024XC	24	6500	10	1760
LARV01S024XN	24	4000	10	1760
LARV01S024XW	24	3000	10	1760

6W Cutout: 75 x 75mm
Height: 35mm

9W Cutout: 75 x 75mm
Height: 33mm

12W Cutout: 106 x 106mm
Height: 33mm

15W Cutout: 106 x 106mm
Height: 33mm

18W Cutout: 158 x 158mm
Height: 33mm

24W Cutout: 208 x 208mm
Height: 35mm

Ensave Plus

LED recess-mounted round downlight with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LESP01R009XC	9	6500	20	1090
LESP01R009XN	9	4000	20	1090
LESP01R009XW	9	3000	20	1090
LESP01R015XC	15	6500	10	1400
LESP01R015XN	15	4000	10	1400
LESP01R015XW	15	3000	10	1400
LESP01R025XC	25	6500	10	2375
LESP01R025XN	25	4000	10	2375
LESP01R025XW	25	3000	10	2375

9W Cutout: Ø97mm
Height: 54mm

15W Cutout: Ø157mm
Height: 80mm

25W Cutout: Ø157mm
Height: 87mm

DOWNLIGHTS

Neve Surface

LED surface-mounted, round panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNVE02R006SC	6	6500	10	850
LNVE02R006SN	6	4000	10	850
LNVE02R006SW	6	3000	10	850
LNVE02R012SC	12	6500	10	1250
LNVE02R012SN	12	4000	10	1250
LNVE02R012SW	12	3000	10	1250
LNVE02R018SC	18	6500	10	1650
LNVE02R018SN	18	4000	10	1650
LNVE02R018SW	18	3000	10	1650

6W Cutout: 90mm
Height: 46mm

12W Cutout: 181mm
Height: 46mm

18W Cutout: 220mm
Height: 54mm

Neve Surface

Surface-mounted, square panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNVE02S006SC	6	6500	10	850
LNVE02S006SN	6	4000	10	850
LNVE02S006SW	6	3000	10	850
LNVE02S012SC	12	6500	10	1250
LNVE02S012SN	12	4000	10	1250
LNVE02S012SW	12	3000	10	1250
LNVE02S018SC	18	6500	10	1650
LNVE02S018SN	18	4000	10	1650
LNVE02S018SW	18	3000	10	1650

6W L x W: 90 x 90mm
Height: 46mm

12W L x W: 181 x 181mm
Height: 46mm

18W L x W: 220 x 220mm
Height: 54mm

DOWNLIGHTS

Volga (Ceiling / Wall Light)

LED surface-mounted, round downlight with PC housing.



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LVOL01R010XC	10	6500	10	1175
LVOL01R010XW	10	3000	10	1175
LVOL01R015XC	15	6500	8	1600
LVOL01R015XW	15	3000	8	1600

10W Dia: 175mm
Height: 70mm

15W Dia: 210mm
Height: 100mm

Turnoe

LED surface-mounted round downlight with in-built driver & polycarbonate diffuser (chrome finish frame)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LZET03R015XC	15	6000	10	1900
LZET03R015XW	15	3000	10	1900

15W Dia: 300mm
Height: 86mm

DOWNLIGHTS

Nero Surface (Round)

LED surface-mounted round panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNRO02R006SC	6	6500	20	800
LNRO02R006SN	6	4000	20	800
LNRO02R006SW	6	3000	20	800
LNRO02R012SC	12	6500	12	1200
LNRO02R012SN	12	4000	12	1200
LNRO02R012SW	12	3000	12	1200
LNRO02R018SC	18	6500	12	1600
LNRO02R018SN	18	4000	12	1600
LNRO02R018SW	18	3000	12	1600

6W Dia: Ø114mm
Height: 30mm

12W Dia: Ø168mm
Height: 30mm

18W Dia: Ø205mm
Height: 30mm

Nero Surface (Square)

LED surface-mounted square panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNRO02S006SC	6	6500	20	800
LNRO02S006SN	6	4000	20	800
LNRO02S006SW	6	3000	20	800
LNRO02S012SC	12	6500	12	1200
LNRO02S012SN	12	4000	12	1200
LNRO02S012SW	12	3000	12	1200
LNRO02S018SC	18	6500	12	1600
LNRO02S018SN	18	4000	12	1600
LNRO02S018SW	18	3000	12	1600

6W L x W: 114 x 114mm
Height: 30mm

12W L x W: 160 x 160mm
Height: 30mm

18W L x W: 195 x 195mm
Height: 30mm

COB-DOWNLIGHTS

Teny

LED recess-mounted COB spot light with aluminium housing (white finish)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTNY01R002XW	2	3000	50	250
LTNY01S002XW	2	3000	50	250

2W Cutout: Ø27mm
Height: 27mm

Estus Fixed

Recess-mounted, COB-based, round fixed LED downlight with 60° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LETS01R010XC	10	6500	20	1475
LETS01R010XN	10	4000	20	1475
LETS01R010XW	10	3000	20	1475
LETS01R020XC	20	6500	10	2500
LETS01R020XN	20	4000	10	2500
LETS01R020XW	20	3000	10	2500
LETS01R030XC	30	6500	10	4200
LETS01R030XN	30	4000	10	4200
LETS01R030XW	30	3000	10	4200

10W Cutout: Ø97mm
Height: 65mm

20W Cutout: Ø121mm
Height: 86mm

30W Cutout: Ø156mm
Height: 96mm

COB-DOWNLIGHTS

Estus Swivel Downlight

Recess-mounted, COB-based, round tiltable LED downlight with multiple beam angles (25° / 36°)



Item Code (36° beam angle)	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LETS36R003XC	3	6500	20	600
LETS36R003XN	3	4000	20	600
LETS36R003XW	3	3000	20	600
LETS36R006XC	6	6500	20	875
LETS36R006XN	6	4000	20	875
LETS36R006XW	6	3000	20	875
LETS36R009XC	19	6500	20	1125
LETS36R009XN	19	4000	20	1125
LETS36R009XW	19	3000	20	1125
LETS36R012XC	12	6500	20	1500
LETS36R012XN	12	4000	20	1500
LETS36R012XW	12	3000	20	1500
LETS36R015XC	15	6500	20	1950
LETS36R015XN	15	4000	20	1950
LETS36R015XW	15	3000	20	1950
LETS36R018XC	18	6500	10	2425
LETS36R018XN	18	4000	10	2425
LETS36R018XW	18	3000	10	2425
LETS36R024XC	24	6500	10	2950
LETS36R024XN	24	4000	10	2950
LETS36R024XW	24	3000	10	2950
LETS36R030XC	30	6500	10	3625
LETS36R030XN	30	4000	10	3625
LETS36R030XW	30	3000	10	3625

3W Cutout: Ø58mm
Height: 50mm

12W Cutout: Ø95mm
Height: 85mm

24W Cutout: Ø118mm
Height: 85mm

6W Cutout: Ø75mm
Height: 65mm

15W Cutout: Ø95mm
Height: 85mm

30W Cutout: Ø118mm
Height: 100mm

9W Cutout: Ø75mm
Height: 65mm

18W Cutout: Ø118mm
Height: 85mm

**Beam angle of 25° is available on request*

COB-DOWNLIGHTS

Estus Swivel Downlight

Recess-mounted, COB-based, square tiltable LED downlight with multiple beam angles (36°)



Item Code (36° beam angle)	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LETS36S003XC	3	6500	20	600
LETS36S003XN	3	4000	20	600
LETS36S003XW	3	3000	20	600
LETS36S006XC	6	6500	20	875
LETS36S006XN	6	4000	20	875
LETS36S006XW	6	3000	20	875
LETS36S009XC	19	6500	20	1125
LETS36S009XN	19	4000	20	1125
LETS36S009XW	19	3000	20	1125
LETS36S012XC	12	6500	20	1500
LETS36S012XN	12	4000	20	1500
LETS36S012XW	12	3000	20	1500
LETS36S015XC	15	6500	20	1950
LETS36S015XN	15	4000	20	1950
LETS36S015XW	15	3000	20	1950
LETS36S018XC	18	6500	10	2425
LETS36S018XN	18	4000	10	2425
LETS36S018XW	18	3000	10	2425
LETS36S0024XC	24	6500	10	2950
LETS36S0024XN	24	4000	10	2950
LETS36S0024XW	24	3000	10	2950
LETS36S0030XC	30	6500	10	3625
LETS36S0030XN	30	4000	10	3625
LETS36S0030XW	30	3000	10	3625

3W Cutout: Ø70mm
Height: 50mm

12W Cutout: Ø95mm
Height: 85mm

24W Cutout: Ø115mm
Height: 100mm

6W Cutout: Ø74mm
Height: 65mm

15W Cutout: Ø95mm
Height: 85mm

30W Cutout: Ø115mm
Height: 100mm

9W Cutout: Ø74mm
Height: 65mm

18W Cutout: Ø115mm
Height: 100mm

COB-DOWNLIGHTS

Ares Focus Light - IP54

Recess-mounted focus lights with aluminium housing, aesthetic finish, compatible with TRIAC dimmers (36° beam angle)

Ares Round 1 fixed with lens optics



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LARS01R013XW	13	3000	10	1800

13W Cutout: Ø70mm
Height: 48mm

Ares Round 2 swivel with lens optics



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LARS02R013XW	13	3000	10	1800

13W Cutout: Ø70mm
Height: 53mm

Ares Round 3 fixed with frosted diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LARS03R013XW	13	3000	10	1900

13W Cutout: Ø60mm
Height: 87mm

LED PANELS

Sauver

Ultra slim LED panel made from extruded aluminium housing frame (recess / pendant) 2ft x 2ft



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSVR01S036XC	36	6000	2	3850
LSVR01S036XN	36	4000	2	3850
LSVR01S036XW	36	3000	2	3850
LSVR01S040XC	40	6000	1	3950

36W/40W Cutout: 596 x 596mm
Height: 9mm

**Accessories separate*

Sauver

Ultra slim LED panel made from extruded aluminium housing frame (recess / pendant) 1ft x 1ft



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSVR01S020XC	20	6000	2	2700
LSVR01S020XN	20	4000	2	2700
LSVR01S020XW	20	3000	2	2700

20W Cutout: 296 x 296mm
Height: 9mm

**Accessories separate*

**Surface mount option available*

Sauver (Surface)

Surface mounted LED panel made from extruded aluminium housing (surface) 2ft x 2ft



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSVR01S036SC	36	6000	1	4850
LSVR01S036SN	36	4000	1	4850
LSVR01S036SW	36	3000	1	4850

36W L x W: 600 x 600mm
Height: 20mm

LED PANELS

Sauver (Linear)

Ultra-slim LED panel made from extruded aluminium housing frame (pendant) 1ft x 4ft



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSVR03S042XC	42	6000	1	5500
LSVR03S042XN	42	4000	1	5500
LSVR03S042XW	42	3000	1	5500

42W L x W: 1200 x 30mm

Height: 9mm

**Surface mount option available*

Ultima

Recess-mounted, white powder-coated CRCA housing with full window acrylic diffuser (2ft x 2ft)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LULT01S042XC	42	6000	2	4000
LULT01S042XN	42	4000	2	4000
LULT01S042XW	42	3000	2	4000
LULT01S036XC	36	6000	2	3650
LULT01S036XN	36	4000	2	3650
LULT01S036XW	36	3000	2	3650

42W/36W Cutout: 596 x 596mm

Height: 60mm

Ultima

Recess-mounted, white powder-coated CRCA housing with full mounted acrylic diffuser (1ft x 1ft)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LULT01S020XC	20	6000	2	2600
LULT01S020XN	20	4000	2	2600
LULT01S020XW	20	3000	2	2600

LED PANELS

Ultima

Recess-mounted, white powder-coated CRCA housing with full mounted acrylic diffuser (1ft x 4ft)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LULT04S036XC	36	4K/5K/6K	2	6000

Ultima Ultra

High Efficacy, recess-mounted, white powder-coated CRCA housing with full mounted acrylic diffuser (2ft x 2ft)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LULTU1S036XC	36	6500	2	4000

Ultima Multicolour

Multicolour changable, recess-mounted, white powder-coated CRCA housing with full mounted acrylic diffuser (2ft x 2ft)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LULT01S036XM	36	3000/4000/6500	2	5000

LED PANELS

Crystic

Contemporary design, suspended light for modern office spaces (Up-downlight) (50:50)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CCRY01S040XN	40	4000	1	13840
CCRY01S040XW	40	3000	1	13840

L x W x H: 1196 x 296 x 9mm

Lattice

Contemporary design, suspended opti-flow linear light for modern office spaces



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LLTC01S040XN	40	4000	1	9200
LLTC01S040XW	40	3000	1	9200

L x W x H: 1180 x 15 x 125mm

Sleek LED Batten

High quality sleek aluminium extruded



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSLM01R009XC	9	6000	30	550
LSLM01R009XW	9	3000	30	550
LSLM01R018XC	18	6000	30	700
LSLM01R018XW	18	3000	30	700

9W L x W: 600 x 56mm
Height: 89mm

18W L x W: 1200 x 56mm
Height: 89mm

LED BATTEN-TUBES

Glaze LED Batten

High quality aluminium extruded with decorative end caps



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGLZ01X010XC	10	6500	20	450
LGLZ01X010XN	10	4000	20	450
LGLZ01X010XW	10	3000	20	450
LGLZ01X020XC	20	6500	20	575
LGLZ01X020XN	20	4000	20	575
LGLZ01X020XW	20	3000	20	575
LGLZ01X024XC	24	6500	20	700
LGLZ01X024XN	24	4000	20	700
LGLZ01X024XW	24	3000	20	700

10W L x W: 535 x 22mm
Height: 37mm

20W L x W: 1195 x 31mm
Height: 40mm

24W L x W: 1195 x 31mm
Height: 40mm

Glaze LED Batten (PC)

High quality design PC batten with decorative end caps



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGLZPCX020XC	20	6500	20	530
LGLZPCX020XW	20	3000	20	530

20W L x W: 1135 x 20mm
Height: 35mm

Glaze LED Batten (PC) Ultra

High quality design PC batten with decorative end caps



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGLZPCX022XC	22	6500	20	700
LGLZPCX022XW	22	3000	20	700

22W L x W: 1165 x 40mm
Height: 44mm

(22w = 2800 lumens)
for 6500K

LED BATTEN-TUBES

T8 Retro LED Tube

Indoor LED tube light, aluminium housing & PC diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTBL01X010XC	10	6000	10	500
LTBL01X010XW	10	3000	10	500
LTBL01X018XC	18	6000	10	575
LTBL01X018XW	18	3000	10	575
LTBL01X020XC	20	6000	10	600
LTBL01X020XW	20	3000	10	600

10W Length: 600mm
Height: Ø30mm

18W Length: 1200mm
Height: Ø30mm

20W Length: 1200mm
Height: Ø30mm

T8 Retro Glass Based

Indoor LED tube light with glass diffuser

Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTBLGLX020XC	20	6500	10	400

20W Length: 1200mm
Height: Ø30mm

T5 Retro - Al - PC based (External Driver)

Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTBLT5X009XC	9	6500	20	660
LTBLT5X014XC	14	6500	20	800

9W Length: 580mm
Height: Ø16mm


14W Length: 1165mm
Height: Ø16mm

DESIGNER LIGHT SERIES



Trius

Uniquely designed, suspended, triangle-shaped with uniform light output. Extruded aluminium with polycarbonate diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTRS02T090XC	90	6000	1	18000
LTRS02T090XN	90	4000	1	18000
LTRS02T090XW	90	3000	1	18000

90W Length: 750mm (each side)
Width: 75mm
Depth: 30mm

Eris Tiltable

Recess-mounted, COB based round adjustable LED downlight with 36° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LERS01R010XC	10	6500	12	1450
LERS01R010XN	10	4000	12	1450
LERS01R010XW	10	3000	12	1450
LERS01R015XC	15	6500	12	2300
LERS01R015XN	15	4000	12	2300
LERS01R015XW	15	3000	12	2300
LERS01R020XC	20	6500	8	3100
LERS01R020XN	20	4000	8	3100
LERS01R020XW	20	3000	8	3100
LERS01R025XC	25	6500	8	3900
LERS01R025XN	25	4000	8	3900
LERS01R025XW	25	3000	8	3900
LERS01R030XC	30	6500	8	4600
LERS01R030XN	30	4000	8	4600
LERS01R030XW	30	3000	8	4600

10W Cutout: 78mm
Height: 82mm

25W Cutout: 138mm
Height: 125mm

15W Cutout: 95mm
Height: 104mm

30W Cutout: 138mm
Height: 125mm

20W Cutout: 115mm
Height: 120mm

Eris Fixed (Low Border Deep Recess)

Recess-mounted, COB based round fixed LED downlight with 36° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LERS02R005XC	5	6500	20	1000
LERS02R005XN	5	4000	20	1000
LERS02R005XW	5	3000	20	1000
LERS02R010XC	10	6500	20	1650
LERS02R010XN	10	4000	20	1650
LERS02R010XW	10	3000	20	1650
LERS02R015XC	15	6500	10	2400
LERS02R015XN	15	4000	10	2400
LERS02R015XW	15	3000	10	2400
LERS02R020XC	20	6500	10	3400
LERS02R020XN	20	4000	10	3400
LERS02R020XW	20	3000	10	3400

8W Cutout: 89mm
Height: 110mm

12W Cutout: 89mm
Height: 110mm

Eris Deep Round

Deep recess-mounted, COB based swivel LED downlight with 38° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LERS03R007XC	7	6500	20	1350
LERS03R007XN	7	4000	20	1350
LERS03R007XW	7	3000	20	1350
LERS03R012XC	12	6500	10	1800
LERS03R012XN	12	4000	10	1800
LERS03R012XW	12	3000	10	1800
LERS03R020XC	20	6500	20	2750
LERS03R020XN	20	4000	20	2750
LERS03R020XW	20	3000	20	2750
LERS03R030XC	30	6500	10	4000
LERS03R030XN	30	4000	10	4000
LERS03R030XW	30	3000	10	4000

7W Cutout: Ø80mm
Height: 68mm

12W Cutout: Ø95mm
Height: 85mm

20W Cutout: Ø120mm
Height: 90mm

30W Cutout: Ø150mm
Height: 98mm

Eris Reflecto

Recess-mounted, COB based LED downlight with anodized reflector of 38°, 43° & 52° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LERS04R007XC	7	6500	50	1500
LERS04R007XN	7	4000	50	1500
LERS04R007XW	7	3000	50	1500
LERS04R012XC	12	6500	10	2000
LERS04R012XN	12	4000	10	2000
LERS04R012XW	12	3000	10	2000
LERS04R020XC	20	6500	20	3000
LERS04R020XN	20	4000	20	3000
LERS04R020XW	20	3000	20	3000
LERS04R030XC	30	6500	20	4300
LERS04R030XN	30	4000	20	4300
LERS04R030XW	30	3000	20	4300

7W Cutout: Ø75mm
Height: 43mm

12W Cutout: Ø97mm
Height: 55mm

20W Cutout: Ø115mm
Height: 65mm

30W Cutout: Ø140mm
Height: 75mm

Eris Deep Square

Deep recess-mounted, COB based swivel LED downlight with 38° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LERS03S007XC	7	6500	20	1350
LERS03S007XN	7	4000	20	1350
LERS03S007XW	7	3000	20	1350
LERS03S012XC	12	6500	10	1800
LERS03S012XN	12	4000	10	1800
LERS03S012XW	12	3000	10	1800
LERS03S020XC	20	6500	20	2750
LERS03S020XN	20	4000	20	2750
LERS03S020XW	20	3000	20	2750
LERS03S030XC	30	6500	10	4000
LERS03S030XN	30	4000	10	4000
LERS03S030XW	30	3000	10	4000

7W Cutout: 80 x 80mm
Height: 68mm

12W Cutout: 95 x 95mm
Height: 85mm

20W Cutout: 135 x 135mm
Height: 105mm

30W Cutout: 170 x 170mm
Height: 115mm

Eris Fixed

Recess-mounted, COB based LED downlight with clear glass of 33°, 45°, 50° & 60° beam angle



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LERS05R007XC	7	6500	50	1400
LERS05R007XN	7	4000	50	1400
LERS05R007XW	7	3000	50	1400
LERS05R012XC	12	6500	40	1900
LERS05R012XN	12	4000	40	1900
LERS05R012XW	12	3000	40	1900
LERS05R020XC	20	6500	10	2700
LERS05R020XN	20	4000	10	2700
LERS05R020XW	20	3000	10	2700
LERS05R035XC	35	6500	10	4300
LERS05R035XN	35	4000	10	4300
LERS05R035XW	35	3000	10	4300
LERS05R050XC	50	6500	10	5200
LERS05R050XN	50	4000	10	5200
LERS05R050XW	50	3000	10	5200

7W Cutout: Ø80mm
Height: 60mm

35W Cutout: Ø185mm
Height: 95mm

12W Cutout: Ø100mm
Height: 65mm

50W Cutout: Ø210mm
Height: 110mm

20W Cutout: Ø130mm
Height: 75mm

Dazzle

Retro fit 4 pin LED PLL with direct plug and play



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LDZL01X020XC	20	6500	20	750
LDZL01X020XW	20	3000	20	750

Rene

Recess-mounted, COB based linear spot light & tempered transparent glass diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LRNE01S002XC	2	6500	60	950
LRNE01S002XN	2	4000	60	950
LRNE01S002XW	2	3000	60	950
LRNE01S006XC	6	6500	48	1600
LRNE01S006XN	6	4000	48	1600
LRNE01S006XW	6	3000	48	1600
LRNE01S010XC	10	6500	40	2400
LRNE01S010XN	10	4000	40	2400
LRNE01S010XW	10	3000	40	2400
LRNE01S020XC	20	6500	25	3950
LRNE01S020XN	20	4000	25	3950
LRNE01S020XW	20	3000	25	3950
LRNE01S030XC	30	6500	20	5700
LRNE01S030XN	30	4000	20	5700
LRNE01S030XW	30	3000	20	5700

2W Cutout: 50 x 47mm
Height: 47mm

6W Cutout: 111 x 47mm
Height: 47mm

10W Cutout: 153 x 47mm
Height: 47mm

20W Cutout: 286 x 47mm
Height: 47mm

30W Cutout: 419 x 47mm
Height: 47mm

GU10

Decorative, energy efficient, flicker free low power consumption bulb



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGU10XX005XC	5	6000	200	400
LGU10XX005XN	5	4000	200	400
LGU10XX005XW	5	2700	200	400
LGU10XX006DC	6	6000	200	500
LGU10XX006DN	6	4000	200	500
LGU10XX006DW	6	2700	200	500
LGU10XX007XC	7	6000	200	475
LGU10XX007XN	7	4000	200	475
LGU10XX007XW	7	2700	200	475

MR16

Decorative, energy efficient, flicker free low power consumption bulb



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LMR16XX007XN	7	4000	200	425
LMR16XX007XW	7	3000	200	425

Zoom Light

Recess-mounted, COB based LED multiple zoom light with anodized reflector & tempered transparent glass diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LZOMMLR115XC	15	6500	40	2800
LZOMMLR115XN	15	4000	40	2800
LZOMMLR115XW	15	3000	40	2800
LZOMMLR135XC	35	6500	12	6000
LZOMMLR135XN	35	4000	12	6000
LZOMMLR135XW	35	3000	12	6000
LZOMMLR215XC	2x15	6500	20	5400
LZOMMLR215XN	2x15	4000	20	5400
LZOMMLR215XW	2x15	3000	20	5400
LZOMMLR235XC	2x35	6500	8	11600
LZOMMLR235XN	2x35	4000	8	11600
LZOMMLR235XW	2x35	3000	8	11600
LZOMMLR315XC	3x15	6500	16	8000
LZOMMLR315XN	3x15	4000	16	8000
LZOMMLR315XW	3x15	3000	16	8000
LZOMMLR335XC	3x35	6500	6	17500
LZOMMLR335XN	3x35	4000	6	17500
LZOMMLR335XW	3x35	3000	6	17500

15W Cutout: 92 x 92mm
Height: 111mm

35W Cutout: 160 x 160mm
Height: 139mm

2 x 15 Cutout: 192 x 92mm
Height: 86mm

3 x 15 Cutout: 270 x 92mm
Height: 86mm

2 x 35 Cutout: 335 x 160mm
Height: 139mm

3 x 35 Cutout: 485 x 160mm
Height: 139mm

DAZY - Trimless

Recess-mounted, COB based LED trimless fixed downlighter & tempered transparent glass diffuser



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LDZY01R008XC	8	6500	36	1600
LDZY01R008XN	8	4000	36	1600
LDZY01R008XW	8	3000	36	1600
LDZY01R012XC	12	6500	27	2100
LDZY01R012XN	12	4000	27	2100
LDZY01R012XW	12	3000	27	2100
LDZY01R018XC	18	6500	22	2900
LDZY01R018XN	18	4000	22	2900
LDZY01R018XW	18	3000	22	2900

8W Cutout: Ø62mm
Height: 94mm

12W Cutout: Ø85mm
Height: 115mm

18W Cutout: Ø100mm
Height: 129mm



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LDZY01S008XC	8	6500	36	1600
LDZY01S008XN	8	4000	36	1600
LDZY01S008XW	8	3000	36	1600
LDZY01S012XC	12	6500	27	2100
LDZY01S012XN	12	4000	27	2100
LDZY01S012XW	12	3000	27	2100
LDZY01S018XC	18	6500	22	2900
LDZY01S018XN	18	4000	22	2900
LDZY01S018XW	18	3000	22	2900

8W Cutout: 60 x 60mm
Height: 98mm

12W Cutout: 75 x 75mm
Height: 115mm

18W Cutout: 100 x 100mm
Height: 131mm

Pit Light

LED pit light with die cast aluminium body with clear PC diffuser (IP66 rating)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LPIT01R016XC	16	6500	20	4400

RETAIL LIGHTING SERIES



Zoom Light

LED recess-mounted, powder-coated die cast aluminium and anodized aluminium reflector



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LZOM01R015XC	15	6500	1	2775
LZOM01R015XN	15	4000	1	2775
LZOM01R015XW	15	3000	1	2775
LZOM01R025XC	25	6500	1	4625
LZOM01R025XN	25	4000	1	4625
LZOM01R025XW	25	3000	1	4625
LZOM01R035XC	35	6500	1	6000
LZOM01R035XN	35	4000	1	6000
LZOM01R035XW	35	3000	1	6000

15W Cutout: 85mm
Height: 72mm

25W Cutout: 140mm
Height: 121mm

35W Cutout: 140mm
Height: 121mm

* CRI > 90 (for 3000k, 4000k only)

Track Light

LED track-mounted, moveable base, round focus light, fully adjustable. Beam Angle 40°. Aluminium Housing (Including Driver Casing)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTRLW1R010XC	10	5000	1	2775
LTRLW1R010XN	10	4000	1	2775
LTRLW1R010XW	10	3000	1	2775
LTRLW1R020XC	20	5000	1	4625
LTRLW1R020XN	20	4000	1	4625
LTRLW1R020XW	20	3000	1	4625
LTRLW1R030XC	30	5000	1	6000
LTRLW1R030XN	30	4000	1	6000
LTRLW1R030XW	30	3000	1	6000



LTRLB1R010XC	10	5000	1	2775
LTRLB1R010XN	10	4000	1	2775
LTRLB1R010XW	10	3000	1	2775
LTRLB1R020XC	20	5000	1	4625
LTRLB1R020XN	20	4000	1	4625
LTRLB1R020XW	20	3000	1	4625
LTRLB1R030XC	30	5000	1	6000
LTRLB1R030XN	30	4000	1	6000
LTRLB1R030XW	30	3000	1	6000

10W Dia: 78mm
Length: 106mm
Height: 195mm

20W Dia: 110mm
Length: 130mm
Height: 198mm

30W Dia: 110mm
Length: 130mm
Height: 198mm

Note: Prices of accessories like track, connecting caps, wires, etc. on request.

Focus Light

Surface mounted, powder coated, die cast aluminium and anodized aluminium reflector with clear diffuser, fully adjustable



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LFCL01R010XC	10	5000	1	2775
LFCL01R010XN	10	4000	1	2775
LFCL01R010XW	10	3000	1	2775
LFCL01R020XC	20	5000	1	4625
LFCL01R020XN	20	4000	1	4625
LFCL01R020XW	20	3000	1	4625
LFCL01R030XC	30	5000	1	6000
LFCL01R030XN	30	4000	1	6000
LFCL01R030XW	30	3000	1	6000
LFCLB1R010XC	10	5000	1	2775
LFCLB1R010XN	10	4000	1	2775
LFCLB1R010XW	10	3000	1	2775
LFCLB1R020XC	20	5000	1	4625
LFCLB1R020XN	20	4000	1	4625
LFCLB1R020XW	20	3000	1	4625
LFCLB1R030XC	30	5000	1	6000
LFCLB1R030XN	30	4000	1	6000
LFCLB1R030XW	30	3000	1	6000

10W L x W x H: 195 x 110 x 106mm

20W L x W x H: 198 x 140 x 130mm

30W L x W x H: 198 x 140 x 130mm

LED Indoor Strip Light (24V DC)

IP33-rated, suitable for indoor applications with different colours and wattages. Standard 5.0 mtr roll



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.) (for 5 mtr)
LSTP03X005XC	25	6000	5	1300
LSTP03X005XN	25	4000	5	1300
LSTP03X005XW	25	3000	5	1300
LSTP03X005XB	25	Blue	5	1300
LSTP03X008XC	40	6000	5	1770
LSTP03X008XW	40	3000	5	1770
LSTP03X015XC	75	6000	5	2140
LSTP03X015XW	75	3000	5	2140
LSTP03X008XM	40	RGB	5	2320
LSTP03X015XM	75	RGB	5	2320

LED Outdoor Strip Light (24V DC)

IP65-rated, suitable for outdoor applications with different colours and wattages. Standard 5.0 mtr roll



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.) (for 5 mtr)
LSTP04X005XC	25	6000	5	1950
LSTP04X005XW	25	3000	5	1950
LSTP04X015XC	75	6000	5	2790
LSTP04X015XW	75	3000	5	2790
LSTP04X008XM	40	RGB	5	3250
LSTP04X015XM	75	RGB	5	4650

Indoor Power Supply for LED strip



Item Code	Wattage (w)	MRP (Rs.)
LDRV01S030XX	30	550
LDRV01S048XX	48	775
LDRV01S060XX	60	900
LDRV01S072XX	72	1100
LDRV01S096XX	96	1700

Outdoor Power Supply for LED strip (IP 65 rated)



Item Code	Wattage (w)	MRP (Rs.)
LDRV02S030XX	30	1375
LDRV02S048XX	48	2575
LDRV02S072XX	72	4225
LDRV02S096XX	96	4775

* RGB controller & amplifier.
Prices on request

INDUSTRIAL LIGHTING SERIES



LED Pride (Weather Proof IP65 Rating)

LED corrosion resistant unbreakable polycarbonate body, dust & water proof



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LPRD01X020XC	20	6000	1	2175
LPRD01X020XW	20	3000	1	2175
LPRD01X040XC	40	6000	1	3275
LPRD01X040XW	40	3000	1	3275

20W L x W x H: 590 x 86 x 67mm

40W L x W x H: 1180 x 86 x 67mm

LED Unilite

LED industrial powder coated MS box with single or twin LED tube.



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LUNI01X120XC	20	6000	1	1100
LUNI01X120XW	20	3000	1	1100
LUNI01X220XC	40	6000	1	1800
LUNI01X220XW	40	3000	1	1800
LRFT01XXXXXX (Reflector)	-	-	1	450

20W L x W x H: 1251 x 47 x 78mm

40W L x W x H: 1251 x 110 x 78mm

Glaze LED Batten

High quality aluminium extruded with decorative end caps



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGLZ01X040XC	40	6500	10	2400

40W L x W x H: 1185 x 25 x 45mm

LED Bulk Head

LED bulk head comprising of pressure die cast housing with acrylic diffuser (IP65 protection)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLK01X010XC	10	6000	1	1650
LBLK01X010XW	10	3000	1	1650

10W L x W x H: 215 x 132 x 55mm

LED Bulk Head

Die cast aluminium housing, opal white PC diffuser, with E27 cap, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CWLL01V109XX	N/A	N/A	1	1450

L: 63mm W: 215mm H: 131mm

LED Highbay Without Glass

Suspended, industrial COB LED highbay. Aluminium die cast heat sink for efficient Heat Dissipation with aluminium reflector



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LHBL120050XC	50	6500	1	7300
LHBL120050XW	50	3000	1	7300
LHBL090070XC	70	6500	1	9100
LHBL090070XW	70	3000	1	9100
LHBL090090XC	90	6500	1	11400
LHBL090090XW	90	3000	1	11400
LHBL090120XC	120	6500	1	13700
LHBL090120XW	120	3000	1	13700
LHBL060150XC	150	6500	1	16500
LHBL060150XW	150	3000	1	16500
LHBL060180XC	180	6500	1	19700
LHBL060180XW	180	3000	1	19700
LHBL060220XC	220	6500	1	22900
LHBL060220XW	220	3000	1	22900

50W/70W/90W/120W Dia: Ø356mm
Height: 265mm

150W/180W/220W Dia: Ø356mm
Height: 305mm

LED Highbay With Glass

Suspended, industrial COB LED highbay. Aluminium die cast heat sink for efficient Heat Dissipation with aluminium reflector

IP65 Rated



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LHBL120050GC	50	6500	1	8200
LHBL120050GW	50	3000	1	8200
LHBL090070GC	70	6500	1	10200
LHBL090070GW	70	3000	1	10200
LHBL090090GC	90	6500	1	12400
LHBL090090GW	90	3000	1	12400
LHBL090120GC	120	6500	1	15000
LHBL090120GW	120	3000	1	15000
LHBL060150GC	150	6500	1	17800
LHBL060150GW	150	3000	1	17800
LHBL060180GC	180	6500	1	21200
LHBL060180GW	180	3000	1	21200
LHBL060220GC	220	6500	1	24700
LHBL060220GW	220	3000	1	24700

50W/70W/90W/120W Dia: Ø356mm
Height: 265mm

150W/180W/220W Dia: Ø356mm
Height: 305mm

ROADWAY LIGHTING SERIES



Trump

LED street light in aluminium pressure die cast housing, polycarbonate cover (IP65 rating)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LTRUMP0025XC	25	6500	1	2450
LTRUMP0025XW	25	3000	1	2450
LTRUMP0030XC	30	6500	1	2900
LTRUMP0030XW	30	3000	1	2900

350mm x 105mm x 60mm

PCR

LED street light in aluminium pressure die cast housing with glass cover & lens** (IP65 rating)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LPCRSRT25WXC	25	6500	1	2550
LPCRSRT25WXW	25	3000	1	2550
LPCRSRT30WXC	30	6500	1	3075
LPCRSRT30WXW	30	3000	1	3075
LPCRSRT36WXC	36	6500	1	3650
LPCRSRT36WXW	36	3000	1	3650

330mm x 117mm x 67mm


Mounting Dia: Ø42mm

**25W - without lens.

Note: All street lights are available with THD <10%

LED Street Light

LED street light in aluminium pressure die cast housing with toughened glass cover (IP66 protection)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSRT01S016XC	16	6000	1	2500
LSRT01S016XW	16	3000	1	2500
LSRT01S018XC	18	6000	1	2600
LSRT01S018XW	18	3000	1	2600
LSRT01S025XC	25	6000	1	2700
LSRT01S025XW	25	3000	1	2700
LSRT01S030XC	30	6000	1	3450
LSRT01S030XW	30	3000	1	3450

16W Mounting Dia: Ø42mm **18W** Mounting Dia: Ø42mm **16W** Mounting Dia: Ø42mm
30W Mounting Dia: Ø42mm

Note: All street lights are available with THD <10%

LED Street Light

LED street light in aluminium pressure die cast housing with touched glass cover (IP66 protection)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSRT01S036XC	36	6000	1	4075
LSRT01S036XW	36	3000	1	4075
LSRT01S045XC	45	6000	1	5075
LSRT01S045XW	45	3000	1	5075
LSRT01S060XC	60	6000	1	6800
LSRT01S060XW	60	3000	1	6800
LSRT01S072XC	72	6000	1	7700
LSRT01S072XW	72	3000	1	7700
LSRT01S090XC	90	6000	1	10000
LSRT01S090XW	90	3000	1	10000
LSRT01S120XC	120	6000	1	12700
LSRT01S120XW	120	3000	1	12700
LSRT01S150XC	150	6000	1	18000
LSRT01S150XW	150	3000	1	18000
LSRT01S200XC	200	6000	1	24500
LSRT01S200XW	200	3000	1	24500
LSRT01S220XC	220	6000	1	27500
LSRT01S220XW	220	3000	1	27500
LSRT01S240XC	240	6000	1	29100
LSRT01S240XW	240	3000	1	29100

36W Mounting Dia: Ø42mm
90W Mounting Dia: Ø85mm
200W Mounting Dia: Ø60mm

45W/60W Mounting Dia: Ø55mm
120W Mounting Dia: Ø62mm

72W Mounting Dia: Ø54mm
150W Mounting Dia: Ø62mm

*for > 50W Street Light

Luxor Street Light

LED street light with high pressure die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LXRSTS060XC	60	6500	1	POR
LXRSTS090XC	90	6500	1	POR

Note: All street lights are available with THD <10%

LED Floodlight

LED flood light with high pressure die cast housing with lens (IP65 protected)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LXRFLDR110XC	110	6500	1	15500
LXRFLDR140XC	140	6500	1	17000
LXRFLDR240XC	240	6500	1	35000
LXRFLDR400XC	400	6500	1	64000
LXRFLDR500XC	500	6500	1	78000
LXRFLDR600XC	600	6500	1	89000
LFLD02S030XC	30	6000	1	4150
LFLD02S030XW	30	3000	1	4150
LFLD02S050XC	50	6000	1	7000
LFLD02S050XW	50	3000	1	7000
LFLD02S070XC	70	6000	1	8800
LFLD02S070XW	70	3000	1	8800
LFLD02S090XC	90	6000	1	11800
LFLD02S090XW	90	3000	1	11800
LFLD02S0120XC	120	6000	1	14500
LFLD02S0120XW	120	3000	1	14500
LFLD02S150XC	150	6000	1	20900
LFLD02S150XW	150	3000	1	20900
LFLD02S180XC	180	6000	1	24600
LFLD02S180XW	180	3000	1	24600
LFLD02S200XC	200	6000	1	27300
LFLD02S200XW	200	3000	1	27300
LFLD02S240XC	240	6000	1	price on request
LFLD02S240XW	240	3000	1	price on request
LFLD02S300XC	300	6000	1	price on request
LFLD02S300XW	300	3000	1	price on request
LFLD02S350XC	350	6000	1	price on request
LFLD02S350XW	350	3000	1	price on request
LFLD02S400XW	400	6000	1	price on request

*for > 50W Street Light

Floodlight

COB-based die cast aluminium housing with toughened glass cover (IP65 protected)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LFLD01S030XC	30	5200	1	4000
LFLD01S050XC	50	5200	1	6200
LFLD01S070XC	70	5200	1	8250

Note: *All SMD type flood lights are available with THD <10%

Luxor Flood Light

Designer LED flood light with efficacy > 110 Lm/W and high pressure die cast housing (for 110 & 140W)

LED flood light equipped with special respirator design and copper pipe heatsink (for 240, 400, 500 & 600W)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LXRFLDS110XC	110	6500	1	15500
LXRFLDS140XC	140	6500	1	17000
LXRFLDR240XC	240	6500	1	35000
LXRFLDR400XC	400	6500	1	64000
LXRFLDR500XC	500	6500	1	78000
LXRFLDR600XC	600	6500	1	89000

LANDSCAPE LIGHTING SERIES



Lyras 65

Decorative LED (3000K) fixture Transparent glass diffuser Narrow beam 30° IP67 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
4699LL5H.BRZ	5	3000	N/A	15400

Lyras 160

Decorative LED fixture Die casting aluminium Diffuser glass transparent Grey Colour Beam 60° IP67



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
4641LL10H.NHG	10	3000	N/A	22300
4641LL20H.NHG	20	3000	N/A	23500
4641LL33H.NHG	33	3000	N/A	25000

Luminz

Die cast aluminium housing, transparent, tempered glass diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK03R104XW	4x1	3000	N/A	3300

Dia: 64mm H: 364mm

NUOVO

Die cast aluminium housing, transparent, tempered glass diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK04R108XW	8	3000	N/A	4300

Dia: 139mm H: 354mm

Sparklz

Die cast aluminium housing, transparent, tempered glass diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK04R112XW	12	3000	N/A	5300

Dia: 108mm H: 440mm

Splash

Die cast aluminium housing, transparent, tempered glass diffuser IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK05R112SW	12	3000	N/A	6500

Dia: 160mm H: 296mm

Illumine

Die cast aluminium housing, transparent, tempered glass diffuser IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK05R112XW	12	3000	N/A	6500

Dia: 160mm H: 511mm

TrueBolt

Aluminium housing, clear glass diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK06R103SW	3	3000	N/A	2700

Dia: 40mm H: 83mm

Dazzler

Aluminium housing, clear glass diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK06R103XW	3	3000	N/A	3300

Dia: 40mm H: 207mm

Ossum

304 stainless steel housing tempered glass diffuser IP68 (12 VAC input)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK68R103SW	3x1	3000	N/A	5600

Dia: 82mm W: 105mm

Insta Ray

304 stainless steel housing tempered glass diffuser IP68 (12 VAC input)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK68R108SW	8x1	3000	N/A	7600

Dia: 160mm H: 225mm

Mira 65

Decorative LED (3000K) fixture Extruded anodized aluminium Diffuser glass transparent 30° Beam angle IP67 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5351LL5H.INX	5	3000	N/A	13200

Mira 65

Decorative LED (3000K) fixture Extruded anodized aluminium Glass diffuser Beam angle 30° IP67 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5383LL5H.INX	5	3000	N/A	13200

Mira 65

Decorative LED fixture Extruded anodized aluminium Glass diffuser IP67 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5382L5H.INX	5	3000	N/A	11900

Mira 65

Decorative LED fixture Extruded anodized aluminium Glass diffuser IP67 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5385LL5H.INX	5	3000	N/A	13400

Mira 65

Decorative LED fixture Extruded anodized aluminium Glass diffuser IP67 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5386LL5H.INX	5	3000	N/A	13700

Mira 150

Decorative LED (3000K) fixture Die casting Aluminium Stainless Steel AISI 316L frame Diffuser glass transparent Wide beam 45° IP67 IK10



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5121LL9H.INX	12	3000	N/A	31600

Mira 220

Decorative LED (3000K) fixture Die casting Aluminium Stainless Steel AISI 316L frame Diffuser glass transparent Wide beam 60° IP67 IK10



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
5521LL20H.INX	20	3000	N/A	31600
5521LL30H.INX	30	3000	N/A	33400

Sublite

Aluminium housing clear PC diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL01R103XW	2	3000	N/A	3100

Dia: 55mm H: 100mm

GLOFLO

Aluminium housing clear PC diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL02R103XW	2	3000	N/A	3100

Dia: 55mm H: 100mm

Huglow

Aluminium housing clear PC diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL03R103XW	2	3000	N/A	3100

Dia: 55mm H: 100mm

ViZi

304 stainless steel ring transparent, tempered glass diffuser IP67



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL04R301XW	3x1	3000	N/A	3250

Dia: 85mm H: 92mm

Zestrum

Die cast aluminium, 304 stainless steel ring transparent, tempered glass diffuser IP67



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL06R601XW	6x1	3000	N/A	4800

Dia: 150mm H: 80mm

DuoLight

Die cast aluminium, 304 stainless steel ring transparent, tempered glass diffuser IP67



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL05R101XW	10x1	3000	N/A	6725

Dia: 175mm H: 94mm

Ikon

Die cast aluminium, 304 stainless steel ring transparent, tempered glass diffuser IP67



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL07R181XW	18x1	3000	N/A	11200

Dia: 260mm H: 94mm

ShineBrite

Die cast aluminium, 304 stainless steel ring transparent, tempered glass diffuser IP67



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGBL08R106XW	6	3000	N/A	3900

Dia: 110mm H: 136mm

Morphis

Decorative LED (3000K) fixture Die casting Aluminium Diffuser glass transparent Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
177.33L24H.NHG	24	3000	N/A	44400
177.33L24H.NHG	E27 (base cap)	3000	N/A	25800

Monaco

Decorative LED (3000K) fixture Die casting Aluminium Diffuser glass transparent Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
340.33.NGG	E27 (base cap)	3000	N/A	7600

Romantica

Decorative LED (3000K) fixture Die casting Aluminium Diffuser polycarbonate frosted Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
350.33L10H.NGG	E27 (base cap)	3000	N/A	22800

Neway

Decorative LED (3000K) fixture Die casting Aluminium Diffuser polycarbonate Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
405.03L10H.NHG	10	3000	N/A	28600

Firenze

Decorative LED fixture Die casting Aluminium Diffuser glass Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
330.33.NGG	E27 (base cap)	3000	N/A	7300

Vibez

Die cast aluminium housing clear PC diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP03X012XW	12	3000	N/A	8100

Dia: 240mm H: 210mm

Orbiss

Die cast aluminium housing frosted PC diffuser, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP01X012XW	24x0.5	3000	N/A	6500

Dia: 248mm H: 300mm

Lugosi

Aluminium housing opal white PC diffuser, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP02X006XW	6x1	3000	N/A	6900

Dia: 240mm H: 300mm

Reneva

MS housing with PU paint top canopy made of spun aluminium, IP65 (IK-10 rated)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP01X030XW	30	3000	N/A	25000
Dia: 600mm H: 600mm				

Pulze

Die cast aluminium housing opal white PC diffuser with E27 cap base, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CBLD03S126XX	26	3000	N/A	3500
L: 194mm W: 194mm H: 265mm				

VeXcel

MS housing with PU paint. Top canopy made of spun aluminium.
Heat resistant toughened bell acrylic diffuser shaped, IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP04X028XW	28	3000	N/A	28000
Dia: 550mm H: 600mm				

Ossio

Cast aluminium housing heat resistant toughended glass, IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP02X030XW	30	3000	N/A	24500
L: 290mm	W: 290mm	H: 653mm		

Lex

Heavy spun aluminium housing. PU paint. Heavy duty heat resistant/toughened acrylic diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWLL01X045XW	45	3000	N/A	26000
Dia: 400mm	H: 650mm			

Vimio

Die cast aluminium body, heat resistant toughened glass diffuser, IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP05X030XW	30	3000	N/A	31000
Dia: 650mm	H: 375mm			

**Poles available in 3.0m, 4.0m, 5.0m heights
(Price on request)*

Morphis

Decorative LED (3000K) fixture Die casting Aluminium Diffuser transparent Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
177.095L24H.NHG	24	3000	N/A	60800

Monaco

Decorative LED fixture Die casting Aluminium Diffuser glass Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
340.44.NGG	E27 (base cap)	3000	N/A	8600

Romantica

Decorative LED fixture Die casting Aluminium Diffuser polycarbonate frosted Black colour IP44



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
350.44L10H.NGG	10	3000	N/A	23800

Neway

Decorative LED (3000K) fixture Die casting Aluminium Diffuser polycarbonate Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
405075L10H.NHG	10	3000	N/A	30600
405K075L10H.NHG	10	3000	N/A	30600

Orion

Decorative LED fixture Die casting Aluminium Diffuser glass Black colour IP44



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
400.075.NHG	E27 (base cap)	3000	N/A	12600

Kubs

Decorative LED (3000K) fixture Die casting Aluminium Diffuser transparent Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
404.070L8X1H.NHG	8	3000	N/A	23800
404.070L4X2H.NHG	2x4	3000	N/A	27300

Titano

Decorative LED fixture Extruded aluminium Diffuser polycarbonate transparent Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
824.075L10H.NHG	10	3000	N/A	33500
824.K075L10H.NHG	10	3000	N/A	35500

Illumitz

Die cast aluminium housing frosted PC diffuser IP65 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD03R108XW	16x0.5	3000	N/A	6375

Dia: 209mm H: 800mm

Zexx

Die cast aluminium housing frosted PC diffuser IP54 with E27 cap base



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CBLD01S126XX	26	3000	N/A	6950

L: 150mm W: 150mm H: 800mm

FabSmart

Die cast aluminium housing opal white PC diffuser IP54 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD04R108XW	16x0.5	3000	N/A	8800

Dia: 145mm H: 800mm

Fruglow

Aluminium housing opal white PC diffuser IP54 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD01R305XW	3x10x0.5	3000	N/A	10900

Dia: 145mm H: 600mm

Orbrix

Die cast aluminium housing tempered glass diffuser IP54 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD02R108XW	8	3000	N/A	8225

Dia: 108mm H: 800mm

Elumx

Die cast aluminium housing opal white PC diffuser IP54 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD05R601XW	6x1	3000	N/A	8625

Dia: 240mm H: 800mm

Visio

Die cast aluminium housing tempered glass diffuser IP54 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD06R108XW	8	3000	N/A	7825

Dia: 145mm H: 600mm

Sirio

Decorative LED fixture Die casting Aluminium Diffuser opal polycarbonate Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
150.01.BGG	E27 (base cap)	3000	N/A	6500
150.01.NGG	E27 (base cap)	3000	N/A	6500

Morphis

Decorative LED (3000K) fixture Die casting Aluminium Diffuser transparent Grey colour IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
175L12H.NHG	12	3000	N/A	26600

Firenze

Decorative LED fixture Die casting Aluminium Diffuser glass Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
330.00.NGG	E27 (base cap)	3000	N/A	6500

Pisa

Decorative LED fixture Die casting Aluminium Diffuser glass Black colour IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
300.00.NGG	E27 (base cap)	3000	N/A	5700

Neway

Decorative LED fixture Die casting aluminium Diffuser polycarbonate Grey Colour IP44



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
405.NHG	E27 (base cap)	3000	N/A	9800

Kubs

Decorative LED (3000K) fixture Die casting aluminium Diffuser transparent Grey Colour
Narrow beam 10° (Up & Down) IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
404LS4X2H.NHG	4x2	3000	N/A	18700
404LL4X2H.NHG	4x2	3000	N/A	18700
404LMA4X2H.NHG	4x2	3000	N/A	18700

Brick Light

Decorative LED (3000K) fixture Recessed mounted Die casting aluminium Diffuser polycarbonate Grey Colour IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
410L6HM.NGG	6	3000	N/A	13600
410M.NGG	6	3000	N/A	5300

Mira 65

Decorative LED (3000K) fixture Recessed mounted Extruded anodized aluminium Diffuser glass opal IP66 IK08



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
4183LL5H.BRZ	5	3000	N/A	13000

Dolby 2

Decorative LED (3000K) fixture Die casting aluminium Diffuser transparent Grey Colour Narrow beam 10° IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
457LL12X1H.NHG	12	3000	N/A	22800
457LL18X2H.NHG	12	3000	N/A	28100

Lyras 130

Decorative LED (3000K) fixture Die casting aluminium Diffuser transparent Grey Colour Medium beam 45° (Up & Down) IP66



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
465LL5X1H.NHG	1x5	3000	N/A	21500
465LL5X2H.NHG	2x5	3000	N/A	25300
460LL9X1H.NHG	1x12	3000	N/A	27100
460LL9X2H.NHG	2x12	3000	N/A	37500

Cervinia

Decorative LED fixture Die casting aluminium Diffuser polycarbonate opal Grey Colour IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
9008.NHG	E27 (base cap)	3000	N/A	9300
9008SEN.NHG	E27 (base cap)	3000	N/A	12600

Acqua

Decorative LED fixture Stainless steel AISI 316L Diffuser polycarbonate opal Auto sensor, Range 1-8mtr (Adjustable) IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
9100SEN.INX	E27 (base cap)	3000	N/A	18900

Twink

Die cast aluminium housing tempered glass diffuser IP65 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01R205XW	2x5	3000	N/A	5625
L: 155mm	W: 108mm	H: 115mm		

Ignix

Die cast aluminium housing tempered glass diffuser IP65 (up light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01R105XW	1x5	3000	N/A	4225
L: 155mm	W: 108mm	H: 115mm		

Leedz

Die cast aluminium housing tempered glass diffuser IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01S203XW	2x3	3000	N/A	4725
L: 78mm	W: 78mm	H: 124mm		

SuperBrite

Die cast aluminium housing tempered glass diffuser IP54 (up light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01S103XW	1x3	3000	N/A	3725
L: 95mm	W: 95mm	H: 95mm		

Brightex

Die cast aluminium housing tempered glass diffuser IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01X208XW	2x8	3000	N/A	7600
L: 136mm	H: 263mm			

Breva

Die cast aluminium housing tempered glass diffuser IP54 (up light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01X108XW	1x8	3000	N/A	4800
W: 120mm	H: 187mm			

Lit'brite

Die cast aluminium housing tempered glass diffuser IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL03X203XW	2x3	3000	N/A	3800
L: 78mm	W: 88mm	H: 124mm		

Lazzo Lit

Die cast aluminium housing transparent tempered glass diffuser IP54 (up light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL03X103XW	1x3	3000	N/A	3000
L: 76mm	W: 95mm	H: 92mm		

Xcellent

Die cast aluminium housing opal PC diffuser IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL02R206XW	2x6	3000	N/A	5500
L: 127mm	W: 140mm	H: 141mm		

ZuperB

Die cast aluminium housing opal PC diffuser IP54 (up light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL02R108XW	1x8	3000	N/A	4300
L: 127mm	W: 141mm	H: 103mm		

BluMon

Die cast aluminium housing SUS304 ring frosted PC diffuser IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBRK01S105XW	10x0.5	3000	N/A	4000
L: 67mm	W: 235mm	H: 73mm		

Meuvo

Die cast aluminium housing transparent tempered glass diffuser IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL04X206XW	2x6	3000	N/A	5600
L: 63mm	W: 125mm	H: 221mm		

GlowLife

Die cast aluminium housing opal white PC diffuser IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBRK02S105XW	10x0.5	3000	N/A	4200
L: 84mm	W: 297mm	H: 54mm		

Lytzon

Die cast aluminium housing transparent, tempered anti-glare diffuser with IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LFLT01S105XW	10x0.5	3000	N/A	4050
L: 54mm	W: 267mm	H: 131mm		

Fluora

Die cast aluminium housing, opal white PC diffuser, with E27 cap base, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CWLL01X118XX	23	3000	N/A	2750
L: 162mm	W: 180mm	H: 248mm		

AmbiView

Die cast aluminium housing, tempered glass diffuser, IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL02X203XW	2x3	3000	N/A	4850
L: 92mm	W: 89mm	H: 208mm		

Brytex

Die cast aluminium housing, opal white PC diffuser, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWLL01X108XW	1x8	3000	N/A	5575
L: 297mm	H: 262mm			

Glitz


Die cast aluminium housing, frosted PC diffuser, with E27 cap base, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CWLL02X113XX	23	3000	N/A	3600
L: 246mm	H: 267mm			

Astre

Die cast aluminium housing transparent tempered glass diffuser IP54 (wall washer)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL03X012XW	1x12	3000	N/A	5800
L: 137mm	W: 137mm	H: 137mm		

Corvell

Die cast aluminium housing transparent tempered glass diffuser IP54 (wall washer)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL04X012XW	1x12	3000	N/A	6600
L: 141mm	W: 145mm	H: 197mm		

Resplendo

Die cast aluminium housing transparent tempered glass diffuser, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LCEL02R112XW	12	3000	N/A	5400
Dia: 145mm	H: 120mm			

WellRay

Molded aluminium tube transparent tempered glass diffuser with E27 cap base, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CCEL01R115XX	15	3000	N/A	1800
Dia: 108mm	H: 190mm			

Monaco

Decorative LED fixture Die casting aluminium Diffuser glass IP43 Base Cap E27



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
340.PE8.NGG	20	3000	N/A	33000

Romantica

Decorative LED (3000K) fixture Die casting aluminium Diffuser glass IP43



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
350.PE8L10H.NGG	10	3000	N/A	45300

Morphis

Decorative LED fixture Die casting aluminium Diffuser glass IP65 Base Cap E27



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
177.300L24H.NHG	24	3000	N/A	49700
177.300.NHG	30	3000	N/A	70000

Morphis

Decorative LED (3000K) fixture Die casting aluminium Diffuser glass IP65



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
178L24H.P1.NHG	24	3000	N/A	74300

Neve Square

LED recess-mounted, square panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNVE02S008XC	8	6000	20	725
LNVE02S008XN	8	4000	20	725
LNVE02S008XW	8	3000	20	725
LNVE02S015XC	15	6000	10	1100
LNVE02S015XN	15	4000	10	1100
LNVE02S015XW	15	3000	10	1100
LNVE02S022XC	22	6000	10	1600
LNVE02S022XN	22	4000	10	1600
LNVE02S022XW	22	3000	10	1600
LNVE02S024XC	24	6000	10	2100
LNVE02S024XN	24	4000	10	2100
LNVE02S024XW	24	3000	10	2100

8W Cutout: 95 x 95mm
Height: 14mm

15W Cutout: 146 x 146mm
Height: 14mm

22W Cutout: 195 x 195mm
Height: 14mm

24W Cutout: 280 x 280mm
Height: 14mm

Neve Round

LED recess-mounted, round panel with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LNVE01R007XC	7	6000	20	725
LNVE01R007XN	7	4000	20	725
LNVE01R007XW	7	3000	20	725
LNVE01R013XC	13	6000	10	1100
LNVE01R013XN	13	4000	10	1100
LNVE01R013XW	13	3000	10	1100
LNVE01R019XC	19	6000	10	1600
LNVE01R019XN	19	4000	10	1600
LNVE01R019XW	19	3000	10	1600

7W Cutout: Ø95mm
Height: 14mm

13W Cutout: Ø163mm
Height: 14mm

19W Cutout: Ø225mm
Height: 14mm

Esquare

LED recess-mounted, square downlight with aluminium die cast housing



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LESQ01S009XC	9	6500	20	1090
LESQ01S009XN	9	4000	20	1090
LESQ01S009XW	9	3000	20	1090
LESQ01S015XC	15	6500	10	1400
LESQ01S015XN	15	4000	10	1400
LESQ01S015XW	15	3000	10	1400
LESQ01S025XC	25	6500	10	2375
LESQ01S025XN	25	4000	10	2375
LESQ01S025XW	25	3000	10	2375


9W Cutout: 97 x 97mm
Height: 54mm

15W Cutout: 141 x 141mm
Height: 74mm

25W Cutout: 141 x 141mm
Height: 80mm

Espot

LED recessed spot light with aluminium housing & prismatic diffuser (white finish)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPT06R002XC	2	6000	20	340
LSPT06R002XW	2	3000	20	340

2W Cutout: Ø32mm
Height: 21mm

Desert Drum

Die cast aluminium housing frosted PC diffuser IP54 with E27 cap base



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CBLD02S126XX	26	3000	1	6000
L: 150mm	W: 75mm	H: 800mm		

Elvin


Die cast aluminium housing, tempered glass diffuser IP65 with GU10 cap base



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LSPK02R105XX	50	3000	1	2850
Dia: 145mm	H: 470mm			

Lxtre

Die cast aluminium housing frosted, tempered anti-glare diffuser with E27 cap base IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CBRK01S140XX	15	3000	1	1500
L: 115mm	W: 256mm	H: 88mm		

Virgo

Die cast aluminium housing, opal white PC diffuser, with E27 cap base, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CWLL03X160XX	15	3000	1	2300
L: 116mm W: 130mm H: 260mm				

Orelli

Die cast aluminium housing transparent tempered glass diffuser, IP54



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LCEL01R112XW	12	3000	1	5400
Dia: 108mm H: 150mm				

Reva

Die cast aluminium housing frosted plastic diffuser IP44 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD09X125XW	12x0.5	3000	1	7600
Dia: 60mm H: 400mm				

Aqua

Die cast aluminium housing opal PC diffuser IP44 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LBLD08X185XW	18x0.5	3000	1	8200
Dia: 220mm H: 500mm				

Xquizit

Die cast aluminium housing opal PC diffuser IP54 (up-down light)



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL01X235XW	2x3.5	3000	1	8000

L: 218mm W: 101mm

Gorzy

Die cast aluminium housing, opal PC diffuser, IP44



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LWWL02X125XW	12x0.5	3000	1	6600

L: 245mm W: 160mm H: 234mm

Lumeno

Die cast aluminium housing clear PC diffuser with E27 cap base, IP44



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
CGTP01X060XX	60	3000	1	3000

Dia: 171mm H: 343mm

Lumeno

Die cast aluminium housing clear PC diffuser IP44 with in-built LED



Item Code	Wattage (w)	CCT (k)	Case No.	MRP (Rs.)
LGTP04X006XW	6	3000	1	5800

W: 171mm H: 343mm



Global Headquarters

Net Zero Energy Building spread over 48,000 sq. mtrs.



Conceived back in 1960, the Jaquar Group has been built on the platform of the highest quality standards, aesthetics and the intent of providing world-class products. Today, the Jaquar Group caters to luxury, premium and value bathroom segments with Artize, Jaquar & Essco brands, respectively, for residential and commercial sectors across the globe.



Artize

It pays a tribute to the fine traditions of exquisite craftsmanship and precision where design, technology and talent combine to deliver a masterpiece. Artize products are crafted for luxurious bath spaces. Perfect harmony is the very essence of Artize- together as coordinates or even as individual pieces. Artize's exquisite craftsmanship is so stunning that it can inspire the design principles of not just your bath spaces but of your entire living spaces.



A leading global super brand known for its excellence in innovation and technology. The highest build standards combine with the most beautifully designed aesthetics to provide world-class products for tough conditions. With a superb blend of ergonomic shapes, contemporary styles and meticulous finish, Jaquar continues to enthral millions of hearts across the world with its wide range of concepts and products.



For over five decades now, Essco, the bath fittings brand, has been supporting affordable and sustainable housing in India. Essco is a value for money bath brand from the Jaquar Group, which is the leader in Complete Bathing Solutions. Essco, a Pan India brand, added a whole new chapter in the bath fittings industry by ushering in the era of the organised bath market. Essco set out with an obsession for good quality products at affordable pricing, one that was unheard of in the corridors of bath fittings manufacturers then. With its 10 years of warranty and impeccable customer service, Essco is standing tall in the Indian bath fittings Industry since 1960 and touching more hearts every year.

JAUAR GROUP

Global Headquarters,
Plot No. 3, Sector-11, IMT Manesar, Gurugram-122050 India
Customer Care - 1800 212 6808 (Toll Free) E-mail : ccare.lighting@jaquar.com
www.jaquarlighting.com

ORIENTATION CENTRES:

AHMEDABAD: Ground Floor, Commerce House-4, B/S Shell Petrol Pump, Near Anand Nagar Cross Roads, 100 Ft. Road, Prahlad Nagar, Satellite, Ahmedabad
Ph.: 079-30452600
Email: ahmedabad@jaquar.com

BANGALORE: No. 10, V.N. Street, Next to Hotel Ramada, Shivaji Nagar, Tasker Town, Bangalore-560051
Email: bangalore@jaquar.com

BHOPAL: T- 7, 8, 3rd Floor, City Center, Above Lotus Electronics, 1 Press Complex, M. P. Nagar, Zone-1, Bhopal- 462011
Ph.: 0755-6550888
Email: bhopal@jaquar.com

BHUBANESWAR: Plot No. 853/1671, 2nd Floor, Jharpada, Cuttack Road, Bhubaneswar-751006
Ph.: 0674-2575501
Email: bhubaneswar@jaquar.com

CHANDIGARH: S.C.O. 52-53, Sector 17-A, Opp. Hotel Park Plaza, Adjacent to Fab India, Chandigarh-160017
Ph.: 0172-4071727
Email: chandigarhoc@jaquar.com

CHENNAI: Ground Floor, KGN Towers, #62, Ethiraj Salai, Egmore, Chennai- 600008
Phone: 044-42693001
Email: chennai@jaquar.com

COCHIN: No. 35/563, Opposite International Stadium, Palarivattom P.O., Cochin-682025
Email: cochin@jaquar.com

GUWAHATI: "Swagota Envision" Ground Floor, G.S. Road, Sixmile, Khanapara (Opp. Directorate of Agriculture, Assam) Guwahati-781022
Email: guwahati@jaquar.com

HYDERABAD: Unit No. 202, Reliance Classic, Banjara Hills, Road No.1, Hyderabad-500034
Email: hyderabad@jaquar.com

JAIPUR: Neelkanth, 1 Bhawani Singh Road, Opp. Nehru Sehkar Bhawan, C-Scheme, Jaipur-302001
Ph.: 0141-5115609
Email: jaipur@jaquar.com

JAMMU: Bonny Square, NH Bypass, Near Vishal Mega Mart, Kunjwani, Jammu-180010
Ph.: 0191-2484876
Email: jammu@jaquar.com

KOLKATA: 2nd Floor, 55, Chowringhee Road, Kolkata-700071
Ph.: 033-40054891
Email: kolkata@jaquar.com

LUCKNOW: Asha Bhawan, 27/II A, Gokhle Marg, Lucknow
Ph.: 0522-4001434
Email: lucknow@jaquar.com

LUDHIANA: 2nd Floor, Lodhi Complex, Mall Road, Ludhiana-141001
Ph.: 0161-5094974
Email: ludhiana@jaquar.com

MUMBAI: 101,102,103, Kamla Spaces, Above Kohinoor Electronics, S.V. Road, Santacruz West, Mumbai-400054
Ph.: 022-26613279
Email: mumbai@jaquar.com

NAGPUR: Kala Bhavan, 103/A, South Ambazari Road, Shradhanand Peth Square, Laxmi Nagar, Nagpur-440022 Ph.: 0712-2223395
Email: nagpur@jaquar.com

NEW DELHI: D-56, Defence Colony, New Delhi-110024
Ph.: 011-24636807
Email: delhincr@jaquar.com

PUNE: DSK Gandharva Heights, 5th Floor, Office No. 501, Near Hotel Pride Executive, Ganeshkhind Road, Shivajinagar, Pune-411005
Email: pune@jaquar.com

RAIPUR: M K Planet, Ring Road No. 1, New Rajendra Nagar, Raipur-492001.
Ph.: 0771-6556789
Email: raipur@jaquar.com

SILIGURI: 1st Floor, M-Square Building, Opp. Hotel Sachitra, 2 ½ Mile, Sevoke Road, Siliguri-734002
Email: siliguri@jaquar.com

SURAT: 23, Siddhi Shopping Centre, Near Agrasen Bhavan Char Rasta, City Light Road, Surat
Email: suratcare@jaquar.com

IP RATING

The 'IP' Code is a standard referred to as International Protection Marking (also commonly interpreted as Ingress Protection Marking) - it rates the inherent degree of 'sealing protection' provided by the mechanical casing/electrical enclosure of a device against intrusion from foreign bodies (e.g. - fingers, tools, wires, insects, dust etc.) and forms of water exposure (e.g. - condensation, droplets, direct spray, full submersion etc.)

IP ratings are a well recognised benchmark (IEC international standard EN 60529) (British BS EN 60529:1992, European IEC 60509:1989) and are applied to many everyday devices - e.g. electronic/electric consumer goods

So what do the numbers mean?

Each IP code has TWO digits to define its level of protection - an "x" is used as one of the digits if there is only one class of protection. The European Standard EN 60529 outlines the IP ratings as an international classification system for "enclosures for electrical equipment" as follows:

The first digit of the IP code indicates the degree that persons are protected against contact with moving parts (other than smooth rotating shafts, etc.) and the degree that equipment is protected against solid foreign bodies intruding into an enclosure.

The second digit indicates the degree of protection of the equipment inside the enclosure against the harmful entry of various forms of moisture (e.g. dripping, spraying, submersion, etc.)

Lighting IP - Rating reference diagram

IP54 = IP Letter Code _____ IP					
1st Digit _____ 5					
2nd Digit _____ 4					
1st Digit	Protection from solid objects		2nd Digit	Protection from moisture	
0	Non protected		0	Non protected	
1		Protected against solid objects greater than 50mm	1		Protected against dripping water
2		Protected against solid objects greater than 12mm	2		Protected against dripping water when tilted up to 15°
3		Protected against solid objects greater than 2.5mmø	3		Protected against spraying water
4		Protected against solid objects greater than 1.0mmø	4		Protected against splashing water
5		Dust protected	5		Protected against water jets
6		Dust tight	6		Protected against heavy seas
<p>Note: EN 60529 does not specify sealing effectiveness against the following: mechanical damage of the equipment; the risk of explosions, certain types of moisture conditions, e.g. those that are produced by condensation; corrosive vapours; fungus; vermin</p>			7		Protected against the effects of immersion
			8		Protected against submersion (see note)

GENERAL CONDITIONS

Prices mentioned are MRPs.

Prices are subject to change without any notice.

Prices of luminaire included in the price list are without lamp/tube except LED.

All products may vary from the photographs shown in this catalogue.

Although every effort has been made to ensure accuracy in the compilation of the technical details in this publication, specifications and performance data are constantly changing. Current details should therefore be checked with Jaquar Group.

Jaquar has an ongoing policy of design, development and improvement, and thus reserves the right to modify the product without any prior intimation.

Jaquar
LIGHTING

